



KANO

GBP 3310KP TB30



Product Features and Key Data

Applications :	Petrol station, gas station, damp places
Luminaire Type :	LED canopy
Mounting Method :	Recessed
Luminaire Optic :	Opal Tempered Glass
Connected Load :	100W
Colour Temperature :	3000K
Rated Luminous Flux :	10000 lm
Luminous Efficiency :	100 lm/W
Power Factor :	> 0,966
CRI Value :	> 80
UGR :	< 21 (EN124664-1)
Photo Biological Class :	Group 0 - No risk
Luminaire Colour :	White color
Luminaire Body :	Luminaire body die cast aluminium
Electrical version :	With electronic transformer, switchable.
Connection method :	Terminal
Mains frequency :	50/60 Hz
Mains voltage :	220 - 240 V
Led Service (25°) :	L80 = 50.000 h
Driver (220 - 240V) :	Tridonic, Osram
Ceiling Type :	AB - Gypsum Ceiling TB - Modular Ceiling KB - Clip-in Ceiling
Ingress Protection (IP) rating :	IP65
Protection class :	I
Impact resistance (IK) :	IK08
Hot wire resistance :	650 °C
Ambient temperature :	-35 - 55 °C
Options :	1 - 3 Hours Emergency Kit, Dali Dimmible
Accessories :	